



FRØYSTAD®

Arctic Power Danline 8-s. Trosse

Diam. i mm	Vekt ca. 110 m	Vekt ca / Mtr	Styrke i TONN	
			m/øye	u/spleis
24	28,7	0,26	11,0	12,22
28	39,2	0,36	14,5	16,11
32	51,0	0,46	18,0	20,00
36	64,5	0,59	22,1	24,56
40	79,0	0,72	27,5	30,59
44	97,0	0,88	32,5	36,11
48	114,0	1,04	38,0	42,22
52	134,0	1,22	44,5	49,44
56	156,0	1,42	50,5	56,11
60	179,5	1,63	56,0	62,22
64	203,5	1,85	65,0	72,22
68	230,5	2,10	73,5	81,67
72	257,5	2,34	82,0	91,11
80	319,0	2,90	100,0	111,11
88	386,0	3,51	120,0	133,33
90	404,0	3,67	126,0	140,00
95	449,0	4,08	140,0	155,56
100	496,5	4,51	155,0	172,22
104	535,0	4,86	163,0	181,11
112	625,0	5,68	202,0	224,44
120	715,0	6,50	230,0	255,56



Fiber: Danline

Lengde: 110m og 220m

Øye standard: 1,8m med kappe

Forlengelse: 17-21%

UV resistent: Normal

Power Danline er siste høyteknologi utvikling, men en styrke som er mer enn 50% høyere enn ISO standard.

- Ingen vanninntrenging
- Enkel håndtering av fortøyning

Produsert ihht. gjeldende ISO std. og testet ihht. ISO 2307.

